

UV-UHO-P1A-M3F4D

Uniarch



Features

- Uniarch
- IP PT camera
- 1/2.8" Progressive Scan CMOS
- 3 Megapixel
- 4 mm Lens
- 0 Lux
- IR range 30 m White light 10 m
- Autotracking
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseTX
- 12 V DC 10 W
- Wifi IEEE802.11b/g/n
- IR Cut
- Built-in microphone and speaker
- Digital WDR
- MicroSD 256 GB
- 3-Axis
- Weatherproof IP66
- Intelligent functions

Specifications

Brand	Uniarch
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304 x 1296)
Lens	4 mm
Main Stream rate	3MP (2304 x 1296), Max 20fps;
Extra Stream rate	640 x 360, Max 20fps;
Compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.005 lux (F2.1 AGC ON) 0 lux with IR on
Infrared range	30 m
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 256 GB
Alarms	Does not have
Audio	Microphone and speaker incorporated
Detection functions	Human body detection, Autotracking, Motion detection, Audio detection, Anti-tampering alarm.
Wi-Fi	IEEE802.11b/g/n
WI-FI frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 10W
Temp. operation	-30° C ~ 60° C
Degree of protection	IP66
Dimensions	Ø118 x 118 x 199 mm
Weight	530 g